(19) World Intellectual Property Organization

International Bureau



(43) International Publication Date 14 July 2005 (14.07.2005)

PCT

(10) International Publication Number WO 2005/064729 A1

(51) International Patent Classification7:

H01M 8/04

(21) International Application Number:

PCT/KR2003/002904

(22) International Filing Date:

30 December 2003 (30.12.2003)

(25) Filing Language:

English


(26) Publication Language:

English

- (71) Applicant (for all designated States except US): LG ELECTRONICS INC. [KR/KR]; 20, Yoido-Dong, Youngdungpo-Gu, 150-010 Seoul (KR).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): CHO, Tae-Hee [KR/KR]; Seongwon Apt. 307-303, Sangnam-Dong, 641-780 Changwon, Gyeongsangnam-Do (KR), PARK, Myung-Seok [KR/KR]; Wooseong Apt. 107-103. 83-3, Pungho-Dong, 645-750 Jinhae, Gyeongsangnam-Do (KR). CHOI, Hong [KR/KR]; Seongwon Apt.
- 308-2204, 45-1, Sangnam-Dong, 641-780 Changwon, Gyeongsangnam-Do (KR). KIM, Kyu-Jung [KR/KR]; Hyundaitown-House Na-101, 236, Gumi-Dong, Bundang-Gu, 463-802 Seongnam, Gyeonggi-Do (KR). LEE, Myeong-Ho [KR/KR]; Cheonggu Apt. 104-1401, 955-2, Jurye 1-Dong, Sasang-Gu, 617-836 Busan (KR), KIM, Cheol-Hwan [KR/KR]; Booyoung Apt. Bugok-Ri, Jangyu-Myeon, 621-833 Gimhae, Gyeongsangnam-Do (KR). HWANG, Yong-Jun [KR/KR]; LG Electronics Dormitory II-324, 14-5, Gaeumjeong-Dong, 641-711 Changwon, Gyeongsangnam-Do (KR). KO, Seung-Tae [KR/KR]; 1450-8, Daemyeong 6-Dong, Nam-Gu, 705-867 Dacgu (KR). HEO, Seong-Geun [KR/KR]; Naraseong Hanvit Apt. 102-905, 3-Ga, Seodaesin-Dong, Seo-Gu, 602-751 Busan (KR),
- (74) Agent: PARK, Jang-Won; Jewoo Bldg. 5th Floor, 200, Nonhyun-Dong, Gangnam-Gu, 135-010 Seoul (KR).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK,

[Continued on next page]

(54) Title: FUEL CELL SYSTEM AND CONTROL METHOD THEREOF



for supplying oxygen-including air to the cathode (4); and a sub fuel cell stack (14) for using hydrogen generated at the anode (2) during reaction as fuel. According to this, energy efficiency of a fuel cell can be increased and danger due to exhaustion of hydrogen generated at the fuel cell stack (6) can be decreased.

WO 2005/064729 A1



MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE,

SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.